

RDM2go



SPECIFICATIONS

Dynamic Effects

- Standalone Color Mixing: Yes
- Color Temperature Presets (Ilumicode): Yes
- Dim Modes (Ilumicode): 5
- Customizable Programs: Yes
- Recall Custom Programs: Yes

Optional Accessories

- DMX Cables

FEATURES

- Handheld tool for managing fixtures and systems with DMX, RDM, and Ilumicode based control
- Easily address, locate and monitor RDM capable fixtures
- Check DMX addressing, cabling, and store/playback basic snapshots
- Address and set personalities of Ilumicode based architectural fixtures
- Comes with connector adaptors, USB charging cord and belt clip pouch

Construction / Physical

- Dimensions: 2.76 x 1.52 x 3.92 in (70 x 39 x 100 mm)
- Weight: 0.77 lb (0.35 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

Connections

- Power Input: Micro USB-B Male
- Data Connectors: 5-pin XLR
- Cable Length (power): 3 ft (0.91 m)

Control

- Protocol(s): DMX, RDM, Ilumicode
- DMX Channels: 1, 2, 3, 4, 5, 6 or 7
- Modes/Personalities (Ilumicode): 13 personalities (ARC 1, ARC 1+D, ARC2, ARC2+D, ARC3, ARC3+D, ARC FULL, REMOTE, SOLID, SPECIAL1, SPECIAL2, VW, VW+D)

Electrical

- Power and Current: 18 W, 0.15 A @ 120 V, 60 Hz
- Power and Current: 18 W, 0.09 A @ 208 V, 60 Hz
- Power and Current: 18 W, 0.08 A @ 230 V, 50 Hz

Certifications / Qualifications

- CE
- IP Rating: IP20, dry location

What's Included

- RDM2go
- Carry Pouch
- 2 pc, 3- to 5-pin converters
- 5-pin male to bare wire adaptor
- USB-A Male to Micro USB-B Male (3 ft)