

64777 CP/92 2000W 230V 12/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54486
Product Name	64777 CP/92 2000W 230V 12/CS 1/SKU
Ordering Abbreviation	64777 CP/92 2000W 230V 12/CS 1/SKU
Brand Name	OSRAM

Electrical data

Nominal Wattage	2000 W
Nominal Voltage	230 V
Type of Current	AC

Light technical data

Luminous Flux	52000 lm
Light Center Length - LCL (in)	3.54 in
Light Center Length - LCL (mm)	90 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	400 h


Physical attributes

Base	G22 MEDIUM BIPOST
Bulb Shape	T10
Length l (in)	6.89 in
Length l (mm)	175 mm
Diameter d (in)	1.378 in
Diameter d (mm)	35.00 mm
Distance a (in)	3.540 in
Distance a (mm)	90 mm

Additional product data

Operating Position	s90
Cooling	CONVECTION

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54486	4008321632197	Folding box (SKU)	1	2.2 in x 2.2 in x 7.5 in	0.3 lb
54486	4008321984241	Shipping box (Case)	12	9.8 in x 8.5 in x 7.6 in	4.5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.