

230V~

50/60Hz
3p=6h
4p+5p=9h

400V~

50/60Hz
3p=9h
4p+5p=6h

Ampere

Poles

Cat.No.

Cat.No.

Event technology

Solid rubber plug

- with screwless cable gland
- dual-point earthing system
- insert: rubber



IP44

05622-ss

Solid rubber connector

- with screwless cable gland
- national
- with hinged lid
- insert: rubber



IP44

25622-ss

3-way connector - solid rubber

- with screwless cable gland
- national
- with hinged lid
- insert: rubber



IP44

253622-sxs

T-Connect

- Equipment:
- 1 CEE-plug 16A 3p 6h
- 1 CEE-socket 16A 3p 6h
- 1 cable entry



IP44 (IP67 available)
other versions on request

94325000

Wall distribution boxes

- many designs available on request
- solid rubber



IP54

Mobile distribution boxes

- many designs available on request
- solid rubber



IP44

Series M-SVE

- shock-resistant, robust and mobile insulated thermo-plastic box
- many designs available on request



IP44

Hinged windows

- available in different dimensions



IP67, IP54

Shark Plug

- with screw terminals
- to order screwless connection technology please add "TT" e.g. 013-6TTx



IP44

Power Twist Plug

- Contact frame with screws



IP66/67

Flanged plug straight

- with screw terminals
- to order screwless connection technology please add "TT" e.g. 613-6TTx



IP44

Shark Connector

- with screw terminals
- to order screwless connection technology please add "TT" e.g. 213-6TTx



IP44

Power Twist Connector

- Contact frame with screws



IP66/67

Flanged socket straight

- with screw terminals
- to order screwless connection technology please add "TT" e.g. 313-6TTx



IP44

Socket outlet (DIN 49440)

- flange 50x50mm
- fixing center 38x38mm
- screwed contact
- available also with Belg./French and British system



IP54

250V~

50/60Hz

16

3

1050-0ss

16

3

1050-0ssw

with sealing bulge